

MAINE TIRE










RUBBER PRESS-ON

Tread Types: Smooth, Traction, DKX and S26

FEATURES

- Endurance Non-Marking tires are designed to operate where clean floors are a priority
- Power Saver greatly reduces rolling resistance for maximum lift truck performance and reduced energy consumption
- MaineTire's all around workhorse compound, Universal, has the industry's highest tensile strength
- Largest footprint provides the lowest per square inch load in the industry, allowing:
 - Lowest rolling resistance
 - Greater shock absorption
 - Less heat build-up
 - More traction
 - Less floor damage
- More tread choices mean more solutions for your material handling needs
- Full shoulder design improves stability

COMPOUNDS

	UNIVERSAL		GLASS KING		OIL RESISTANT
	POWER SAVER		WIRE TEX		STATIC CONDUCTING
	ENDURANCE NON-MARKING		GRIP SHELL		TWR-TEAR WEAR RESISTANT

LEGEND

T - Traction
 S - Smooth
 D - DKX traction
 S26 - Wide Profile Traction

Smooth



Traction



Endurance Non-Marking



MAINTIRE**RUBBER PRESS-ON**

Tread Types: Smooth, Traction, DKX and S26

SPECS

SIZE	L.R.(lbs) 10mph	Type	L.R.(lbs) 6mph	Wt.
8 x 4 1/2 x 4 1/2	1390	S	1580	10
8 1/2 x 4 x 4	1260	S	1430	10
9 x 2 1/2 x 6	710	S	810	6
9 x 5 x 5	1740	S	1960	13
10 x 3 x 6 1/4	970	S	1100	9
10 x 3 x 6 1/2	970	S	1100	9
10 x 3 1/2 x 6	1200	S	1350	11
10 x 3 1/2 x 8	1170	S	1320	10
10 x 4 x 5	1420	S,T	1610	13
10 x 4 x 6 1/4	1420	S	1610	12
10 x 4 x 6 1/2	1420	S	1610	12
10 x 4 3/4 x 6 1/2	1760	S,T	1990	15
10 x 5 x 6 3/16	1880	S	2120	16
10 x 5 x 6 1/4	1880	S	2120	16
10 x 5 x 6 1/2	1840	S,T	2070	15
10 x 5 x 6 1/2 Contour	1840	S	2070	15
10 x 5 x 6 1/2	1840	S,T	2070	15
10 x 6 x 6 1/4	2300	S	2600	19
10 x 6 x 6 1/2	2330	S	2630	19
10 x 7 x 6 1/4	2750	S	3100	22
10 1/2 x 3 1/2 x 8	1210	S	1370	11
10 1/2 x 4 x 6 1/2	1470	S	1660	13
10 1/2 x 4 1/2 x 8	1650	S	1860	14
10 1/2 x 5 x 5	1990	S	2250	17
10 1/2 x 5 x 5	1990	T	2250	17
10 1/2 x 5 x 5 Contour	1990	S	2250	17
10 1/2 x 5 x 6 1/2	1940	S	2200	17
10 1/2 x 5 x 6 1/2	1940	T	2200	17
10 1/2 x 5 1/2 x 8	2130	S	2410	18
10 1/2 x 6 x 5	2530	S	2860	21
10 1/2 x 6 x 5	2530	T	2860	21
10 1/2 x 6 x 6 1/4	2410	S	2730	21
10 1/2 x 6 x 6 1/2	2410	S,T	2730	20
10 1/2 x 7 x 6 1/2	2890	S	3270	24
11 x 5 x 6 1/2	2060	S	2330	18

SPECS

SIZE	L.R.(lbs) 10mph	Type	L.R.(lbs) 6mph	Wt.
12 x 3 1/2 x 8	1370	S	1550	14
12 x 4 x 8	1630	S	1850	16
12 x 4 1/2 x 8	1890	S,D	2140	18
12 x 5 1/2 x 8	2410	S	2740	22
12 x 6 1/2 x 8	2930	S	3340	27
12 x 7 1/4 x 8 5/8	3060	S	3460	29
13 x 3 1/2 x 8	1430	S	1610	16
13 x 4 1/2 x 8	2030	S,T	2300	21
13 x 5 1/2 x 9 1/2	2730	S	3080	21
13 1/2 x 4 1/2 x 8	2080	S,T,D	2350	22
13 1/2 x 5 x 8	2390	S	2700	25
13 1/2 x 5 1/2 x 8	2730	S-26	3080	28
13 1/2 x 5 1/2 x 8	2730	T	3080	28
13 1/2 x 5 1/2 x 8	2730	D	3080	28
13 1/2 x 5 1/2 x 8	2730	S	3080	28
13 1/2 x 5 1/2 x 9 1/2	2670	S	3020	28
13 1/2 x 5 1/2 x 10	2730	S	3080	25
13 1/2 x 6 1/2 x 8	3390	S,T	3830	33
14 x 4 x 10	1830	S	2068	19
14 x 4 1/2 x 8	2120	S-26	2390	24
14 x 4 1/2 x 8	2120	S	2390	24
14 x 5 x 10	1880	S	2120	25
14 x 6 x 10	1930	S	2180	31
15 x 3 x 11 1/4	1310	S	1480	15
15 x 3 1/2 x 11 1/4	1620	S	1830	18
15 x 4 x 11 1/4	1930	S	2170	21
15 x 5 x 11 1/4	2520	S,T	2850	27
15 x 6 x 11 1/4	3120	S	3530	32
15 x 6 x 11 1/4	2610	T	2950	32
15 x 7 x 11 1/4	3720	S,T	4210	38
15 x 8 x 11 1/4	4320	S	4890	44
15 x 8 x 11 1/4	4320	T	4890	44
15 x 9 x 11 1/4	5000	S	5650	49
15 1/2 x 5 x 10	2670	S,T	3010	30
15 1/2 x 6 x 10	3380	S,T	3820	37

MAINTIRE RUBBER PRESS-ON

Tread Types: Smooth, Traction, DKX and S26

SPECS				
SIZE	L.R.(lbs) 10mph	Type	L.R.(lbs) 6mph	Wt.
16 x 2 1/2 x 13 3/4	1200	S	1360	20
16 x 3 1/2 x 12	1700	S	1920	20
16 x 3 1/2 x 12 1/8	1700	S	1920	20
16 x 4 x 12 1/8	2020	S,T	2290	23
16 x 4 1/2 x 12	2340	S	2660	26
16 x 4 1/2 x 10 1/2	2360	S,T	2670	28
16 x 4 1/2 x 12 1/8	2340	S,T	2640	26
16 x 5 x 10 1/2	2730	S,T,S-26	3090	32
16 x 6 x 10 1/2	3460	S,T,D	3920	39
16 x 7 x 10 1/2	4200	S,T	4750	46
16 1/4 x 4 x 11 1/4	2040	S,T	2310	25
16 1/4 x 5 x 11 1/4	2760	S,T,S-26	3120	32
16 1/4 x 6 x 11 1/4	3480	S,T	3930	39
16 1/4 x 7 x 11 1/4	4190	S,T	4740	45
16 1/4 x 8 x 11 1/4	4900	S,T	5540	52
17 x 4 1/2 x 12 1/8	2480	T	2810	30
17 x 5 x 12 1/8	2850	S,T	3220	33
17 x 6 x 12 1/8	3590	S,T	4080	40
17 x 7 x 11 15/16	4330	S	4080	48
17 x 7 x 12 1/8	4320	S,T	4870	48
17 3/4 x 5 x 12 1/8	2940	S,T	3320	37
17 3/4 x 6 x 12 1/8	3760	S	4240	45
17 3/4 x 6 x 12 1/8	3760	T	4240	45
18 x 4 x 14	2210	S	2500	27
18 x 5 x 12 1/8	2980	S,T,S-26	3360	38
18 x 5 x 14	2910	S	3290	34
18 x 6 x 12 1/8	3800	S,T,D	4290	46
18 x 7 x 12 1/8	4620	S,T,D	5220	54
18 x 7 x 14	4320	S	4890	48
18 x 8 x 12 1/8	5440	S,T,D	5150	63
18 x 8 x 14	5030	S	5680	56
18 x 9 x 12 1/8	6270	S,T,D	7080	71
18 x 9 x 14	5730	S	6480	63
18 x 12 x 14	7840	S	8910	85
20 x 3 1/2 x 16	2010	S	2270	26

SPECS				
SIZE	L.R.(lbs) 10mph	Type	L.R.(lbs) 6mph	Wt.
20 x 4 x 16	2390	S	2690	30
20 x 5 x 16	3150	S,T	3560	38
20 x 6 x 16	3920	S,T	4440	47
20 x 7 x 16	4680	S,T	5340	55
20 x 8 x 15	5730	S	6480	69
20 x 8 x 16	5460	S,T	6170	63
20 x 9 x 15	6520	S	7430	78
20 x 9 x 16	6210	S,T	7010	71
20 1/2 x 7 x 17 3/4	4330	S	4890	50
21 x 5 x 15	3330	S,T	3770	46
21 x 6 x 15	4270	S,T	4820	57
21 x 7 x 15	5200	S,T,D	5870	67
21 x 8 x 15	6130	S,T,D	6930	77
21 x 9 x 15	7060	S,T,D	7980	87
21 x 12 x 15	9850	S	11130	119
22 x 3 1/2 x 17 3/4	2160	S	2440	30
22 x 4 1/2 x 17 3/4	2980	S	3350	39
22 x 5 x 16	3450	S,T	3990	49
22 x 6 x 16	4420	S,T	4990	60
22 x 6 x 17 3/4	4210	S,T	4820	53
22 x 7 x 16	5380	S,T	6080	71
22 x 7 x 17 3/4	5020	S,T	5670	63
22 x 8 x 16	6340	S,T,D	7170	82
22 x 8 x 17 3/4	5840	S,T	6600	72
22 x 9 x 16	7310	S,T,D	8260	92
22 x 10 x 16	8270	S,T	9350	103
22 x 10 x 17 3/4	7480	S	8560	91
22 x 11 x 16	9220	S	10420	114
22 x 12 x 16	10200	S,T	11530	125
22 x 12 x 17 3/4	10400	T	11750	109
22 x 14 x 16	12130	S,T	13710	146
22 x 14 x 17 3/4	12330	T	13930	128
22 x 16 x 16	14050	S	15890	168
23 3/4 x 6 x 17 3/4	4690	S	5300	66
24 x 4 x 20	2740	S	3100	37

MAINE TIRE RUBBER PRESS-ON

Tread Types: Smooth, Traction, DKX and S26

SPECS

SIZE	L.R.(lbs) 10mph	Type	L.R.(lbs) 6mph	Wt.
24 x 7 x 20	5360	S	6060	68
26 x 5 x 20	3910	S,T	4420	60
26 x 7 x 20	6100	S,T	6890	87
26 x 8 x 20	7180	S	8110	108
28 x 10 x 22	9910	S	11200	138
28 x 12 x 22	12220	S,T	13820	167
28 x 14 x 22	14530	S	16430	196
28 x 16 x 22	16840	S	19040	225
36 x 10 x 30	11970	S	13530	185
36 x 12 x 30	14760	S	16680	223
36 x 14 x 30	17520	S	19800	262
36 x 16 x 30	20330	S	22900	300

TREAD SURFACE TREATMENTS

The custom tread treatments shown below are available as Special Factory Orders only on Smooth press-on tires only.



Siping: Lateral 1/2" deep razor cuts are made 1/2" apart on smooth tread to provide extra traction on wet surfaces and inclines. Note that this treatment voids tire warranty.



Cross Grooving: 3/16" wide diagonal grooves are cut into smooth tire surfaces to channel out water and reduce hydroplaning.












Diamond Cutting: Criss-crossing grooves are cut into smooth tire surfaces - typically used for sweeper tires operating in very wet conditions.



Grooving: A 5/8" wide and 5/8" deep groove is cut into smooth tread tire surfaces to reduce steer tire side slipping and drive tire heat build-up.

COMPOUNDS

 UNIVERSAL	 GLASS KING	 OIL RESISTANT
 POWER SAVER	 WIRE TEX	 STATIC CONDUCTING
 ENDURANCE NON-MARKING	 GRIP SHELL	 TWR-TEAR WEAR RESISTANT

LEGEND

T - Traction
S - Smooth
D - DKX traction
S26 - Wide Profile Traction

Smooth



Traction



Endurance Non-Marking



**MAINE
INDUSTRIALTIRE**