

itl[®] MAXMATIC

WIDE PROFILE NON-SKID

CONSTRUCTION

The Maxmatic Tire with its aggressive tread pattern is designed as an all season drive tire to provide maximum traction in both in-plant and outdoor uses.

FEATURES

- More rubber provides longer tread life
- Wider tread profile offers better stability
- Self-cleaning tread design includes siping for channeling water away from the tread face
- Larger footprint provides significantly better traction over standard traction press-on tires
- Up to a 20% increase in carrying capacity. (depending upon application)
- Improves stability, traction, flotation, load capacity, and reduces driver & equipment fatigue

SPECS

SIZE	LOAD CAP. (lbs) 6 mph	Wt.
10 x 5 x 6 1/2	2070	18
13 x 4 1/2 x 8	2300	20
16 x 6 x 10 1/2	3920	41
16 1/4 x 6 x 11 1/4	3930	39
16 1/4 x 7 x 11 1/4	4740	44
18 x 6 x 12 1/8	4290	46
18 x 7 x 12 1/8	5220	59
18 x 8 x 12 1/8	6150	63
18 x 9 x 12 1/8	7080	70
21 x 5 x 15	3770	46
21 x 6 x 15	4820	53
21 x 7 x 15	5870	66
21 x 8 x 15	6930	74
21 x 9 x 15 *	7980	87
22 x 8 x 16	7170	79

* Offered in MITL brands only

COMPOUNDS



FOOTPRINT



MAXMATIC

Net Area

24 sq. in.

Deflection

0.38 in.



CONVENTIONAL NONSKID

Net Area

18 sq. in.

Deflection

0.55 in.

ADVANTAGE

Using a 21 x 7 x 15 Maxmatic offers approximately 6 sq. inches more contact than a conventional non-skid & almost 30% less deflection resulting in less heat build up.

